Material Safety Data Sheet



NFPA



HMIS

Health Hazard	0
Fire Hazard	1
Reactivity	0

Issuing Date 28-June-2010 Revision Date 28-June-2010 Revision Number

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name O'REILLY MULTI-PURPOSE GL-5 GEAR LUBRICANT 80W90 AND 85/140

Product Code

Recommended Use

Manufactured by: Omni Specialty Packaging

10399 S. Hwy 1 Shreveport, LA 71105 Phone: 1 (318) 524-1100

Emergency Telephone Number CHEMTREC

1 (800) 424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

AppearanceAmber LiquidPhysical StateLiquidOdorMild petroleum odor

Potential Health Effects

Principal Routes of Exposure Eye contact, Skin contact, Inhalation, Ingestion

Acute Toxicity

Eyes Eye contact may result in slight irritation and redness..

Skin Minimally irritating upon direct contact.

Inhalation Low hazard at standard temperatures and pressures. Inhalation of oil mist or

fumes can cause irritation of the nose, throat and upper respiratory tract

Ingestion Do not ingest. May cause nausea, vomiting/diarrhea.

Other On rare occasions, prolonged and repeated exposure to oil mist poses a risk of

pulmonary disease such as chronic lung inflammation. This condition is usually

asymptomatic as a result of repeated small aspirations.

Chronic Effects Prolonged exposure may cause chronic effects.

Aggravated Medical Conditions Personnel with pre-existing skin disorders should avoid contact with this product.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula Mixture

Chemical Name	CAS-No	Weight %
Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum)	64742-65-0	40-85
Hydrotreated Distillates, Heavy Paraffinic	64742-54-7	5-25
Additive Package	Mixture	10-40
Pour Point Depressant	N/A	0-5

4. FIRST AID MEASURES

Eye Contact Flush with large amount of water for 15 minutes. Get medical attention if eye irritation

develops or persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes while removing all

contaminated clothing and shoes. Get medical attention immediately if skin discoloration

occurs.

Inhalation If affected, remove individual to fresh air. If not breathing, give mouth-to-mouth resuscitation.

Get medical attention if symptoms develop or persist.

Ingestion CALL PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious

person.Don't induce vomiting except at the instructions of the physician.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable.

Flash Point 430°F

Suitable Extinguishing Media Water Fog. Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media Water stream may spread fire.

Hazardous Combustion Products Decomposition and combustion products may include

smoke, carbon dioxide, carbon monoxide, and other low

molecular weight hydrocarbons.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive.
Sensitivity to Static Discharge Not sensitive.

Protective Equipment and Precautions for Firefighters Wear positive pressure self-contained breathing

apparatus (SCUBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal flash point.

NFPA Health Hazard 0 Flammability 1 Reactivity 0 Physical and Chemical Hazards

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Avoid contact with skin, eyes, and clothing.

Ensure adequate ventilation.

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be

absorbed on inert material.

Evacuation Procedures

Large Spill Fire Consider initial downwind evacuate for at least 300 meters (1000 feet).

If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Reporting Requirements Spills that enter a water body must be reported immediately to the USEPA's National

Response Center at (800)546-2972. Check with your local and state regulators

regarding their reporting requirements.

7. HANDLING AND STORAGE

Handling Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame,

sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and

OSHA 1910.106 - flammable and combustible liquids.

Storage Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly

labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be

dangerous

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0	5 mg/m³ TWA (mist)	5 mg/m³ mist	2,500 mg/m³
Hydrotreated Distillates, Heavy Paraffinic 64742-54-7	5 mg/m³ TWA (mist)	5 mg/m³ mist	2,500 mg/m³

Engineering Measures Additional area ventilation or local exhaust may be required to maintain air

concentrations below recommended limits.

Personal Protective Equipment

Eye/Face Protection Safety glasses or face shield where splashing is possible. Full face-shield to be

worn during emergencies.

Skin and Body Protection As needed to prevent repeated skin contact. Solvent resistant gloves should

be used if needed.

Respiratory Protection Not normally needed. During emergencies wear respirator.

Hygiene Measures Remove and wash contaminated clothing before re-use. Wash hands before

breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceAmber LiquidOdorMild petroleum odorPhysical StateLiquidpHN/A

Liquid N/A **Flash Point** 430°F **Autoignition Temperature** 729°F **Boiling Point/Range** 829°F **Melting Point** 32°F **Explosion Limits** Flammability Limits in Air N/A N/A **Specific Gravity** Solubility 0.89 Negligible

Evaporation Rate N/A Vapor Pressure N/A Vapor Density Not Determine Density N/A

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible ProductsOpen Flame and strong oxidizing agents.

Conditions to Avoid Heat, flames, and sparks.

Hazardous Decomposition Products Decomposition and combustion products may include smoke, carbon

dioxide, carbon monoxide, and other low molecular weight hydrocarbons.

Hazardous PolymerizationNone under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product InformationTest on similar materials show a low order of acute oral and dermal toxicity.

Acute Oral Effects Test on similar materials indicates low order of acute toxicity.

Acute Inhalation

Low acute toxicity expected on inhalation.

Effects Skin Effects

ects Practically non-toxic if absorbed. Other similar highly refined products have not shown

skin tumors in mouse skin painting studies.

Eye Irritation Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on

similar products.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0	Rat >2000 mg/kg	Rabbit >2000 mg/kg	Rat > 2.18 mg/L 4 hours
Hydrotreated Distillates, Heavy Paraffinic 64742-54-7			

Chronic Toxicity

Chronic Toxicity Prolonged exposure may cause chronic effects.

Carcinogenicity Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

Target Organ Effects Respiratory system, Eyes, Skin,

Genotoxicity This product is considered non-mutagenic and has negative potential for tumor

development based on from Modified Ames Assay, with Mutagenic Index of less than

1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity

If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)
Heavy Hydrotreated				
Naphthenic				
Distillates				
(petroleum)				
64742-52-5				
Hydrotreated				
Distillates, Heavy				
Paraffinic				
64742-54-7				

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers and

waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

Chemical Name	RCRA – Halogenated Organic Compounds	RCRA – P Series Wastes	RCRA – F Series Wastes	RCRA – K Series Wastes
	Does not meet	Does not meet	Does not meet	Does not meet
	hazardous waste	hazardous waste	hazardous waste	hazardous waste
	criteria	criteria	criteria	criteria

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

	TSCA	DSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Solvent-Dewaxed Heavy Paraffinic Distillates (Petroleum) 64742-65-0	Present	Х	265-169-7	Х	Х	Х	X	X
Hydrotreated Distillates, Heavy Paraffinic 64742-54-7	Present	X	265-157-1	X	X	X	X	X

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Florida

No listed ingredients are present

Massachusetts RTK

No listed ingredients are present

Minnesota RTK

No listed ingredients are present

New Jersey RTK

Lists petroleum oil, but this product does not contain hazardous ingredients.

Pennsylvania RTK

Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%.

Illinois DOL TSL

No listed ingredients are present

International Regulations

Mexico – Grade No information available.

Canada Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with

Controlled Products Regulation

CONEG Metals Since cadmium, chromium, lead and mercury are not detectable and it does not exceed

100 ppm total in this product, it is compliant with CONEG Metals regulation.

EEC (Europe) This product is not known to be a dangerous good internationally.

R-Phrases R45: May Cause Cancer S-Phrases S53: Avoid Exposure S45

Hazard Label None Danger Symbol T : Toxic

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials

16. OTHER INFORMATION

Prepared By Safety Department

Issuing Date 28-June -2010

Revision Date 28-June-2010

Revision Note Not applicable

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS